

Hisense International Co., Ltd.

Add: Hisense International Center, No. 88 Xianggang East Road, Qingdao, China E-mail: marketing@hisense.com Website: http://www.hisense.cn/en

Add: 08 Ronggang Road, Ronggui, Shunde, Guangdong, China. E-mail: marketing@hisense.com Website: http://www.hisense.cn/en

Note: Product design and specification subject to change without prior notice.

© 2025 Hisense Corporation. All rights reserved. Hisense and the Hisense logo are trademarks or registered trademarks of Hisense Group in China and/or other countries. All rights reserved. The Hisense Smart TV logo, Ultra HD High Definition logo, SMR logo and life reimagined logo are trademarks or registered trademarks of Hisense Electric Co., Ltd. in China and/or other countries. All rights reserved. All other company names, brand names,

trademarks and logos are the property of their respective owners. All rights reserved.

Hisense

Hi-Therma II

R299 Heat Pump Product Catalogue



Reimagine your solution



Hisense SINCE 1969

Hi-Therma II

Hisense is a well–known large–scale electronic information industrial group. With strong emphasis on technology and innovation, its efficient technological innovation system firmly grounds Hisense at the forefront of its peers. At present, Hisense brand family has expanded to include multiple famous brand Hisense, Toshiba, Gorenje and ASKO.

BUSINESS OVERVIEW

Multimedia •

TV and Display Devices Internet TV Operation Mobile Communication Devices Optical Communication Devices Chip

Household • Appliances

Refrigerator Freezer Air-conditioner Washing Machine Kitchen Appliance

IT Smart Systems •----


Smart City Smart Community Smart Transportation Smart Business Medical Electronic Devices Smart Home System and Service

Real Estate & •--Modern Services

Real Estate
High-end Shopping Mall Chain
Mould Design and Manufacturing
Finance
Trade










GLOBAL HISENSE SINCE 1969

Hisense has started a long-term sports marketing strategy to increase brand awareness worldwide.

After the successful sponsorship of **UEFA EURO 2016 & 2020** and **FIFA WORLD CUP 2018 & 2022**, Hisense has made clear its focus on football. Hisense also is the official partner of **UEFA EURO 2024**.










The ATW heat pump system is a revolutionary solution for cooling, heating and domestic hot water. It converts renewable energy sources like air, soil and water into useful heat through an refrigerant cycle, which is more energy—efficient and eco—friendly than traditional fossil fuel boilers.

Advanced Renewable Energy Utilization Technology

Thanks to the advanced heat pump technology, Hi–Therma II Series can pump heat from the natural air source with a small amount of electricity used, and then supply a large amount of heat to your home. The heat output is greater than the electricity input, making the system highly efficient.





Sustainable Alternative to Conventional Boilers

Traditional heating systems rely on fossil fuels like gas, oil, and coal, which have caused heavy environmental pollution and greenhouse gas emissions. Hi–Therma II Series has been developed to meet the increasing demand for eco–conscious devices in both newly–built and renovated homes, reducing environmental impact and minimizing energy consumption to the greatest extent.



Hi-Therma II Reimagine your solution





Domestic Hot Water



Radiator Heating

Fan Coil Unit Cooling&Heating

03 -- 04




F-Gas Regulation

European regulation F-GAS (517/2014) came into force on 1st January 2015, in order to reduce greenhouse gas emissions. It aims to reduce the environmental impact of F-gases through the reduction of the amount of HFC (hydrofluorocarbon) refrigerant used in cooling and heating systems.

The regulation 517/2014 prescribes a phase-down of HFCs, where the quantities of HFCs that are placed on the market are gradually reduced through the allocation of quotas by the European Commission. The phase-down targets are expressed in CO₂ equivalents (= kg x GWP- Global Warming Potential) and aim to reduce HFC consumption by 79% in 2030.

Consumption of HFC compared to CO2 equivalent tonnes



KEYMARK Certifcate

The Heat Pump KEYMARK is a voluntary, independent European certification mark (ISO type 5 certification) for all heat pumps, combination heat pumps and hot water heaters (as covered by Ecodesign, EU Regulation 811/2013 and 813/2013).

It is based on independent, third party testing and demonstrates compliance with product requirements as set in the Heat Pump KEYMARK scheme rules and with efficiency requirements as set by Ecodesign.

The Heat Pump KEYMARK scheme is owned by the European Committee for standardization (CEN). The certificates are granted by independent Certification Bodies to products fulfilling all requirements of the scheme.

Check all our certified heat pumps on: www.heatpumpkeymark.com




05 –

Product Lineup Overview

Series		Hi-Therma II R290				
Туре	M1 Series	H1 Series				
Diagram		**************************************				
Soution	Monobloc	Hydro-split	Hydro-integra			
Line-up	1 phase 5.0/8.0/10.0kW	1 phase 5.0/8.0/10.0kW	1 phase 5.0/8.0/10.0kW			
Application						
Energy Label Space Heating 35℃	A+++	A+++	A+++			
Energy Label Space Heating 55℃	Up to A+++	A++	A++			

Series	Hi-Therma II R290							
Туре	M2 Series	H2 Series						
Diagram	Coming soon	Coming Soon	Coming soon					
Soution	Monobloc	Hydro-split	Hydro-integra					
Line-up	1 phase/3 phase 12.0/14.0/16.0kW	1 phase/3 phase 12.0/14.0/16.0kW	1 phase/3 phase 12.0/14.0/16.0kW					
Application								
Energy Label Space Heating 35℃	A+++	A+++	A+++					
Energy Label Space Heating 55℃	A++	A++	A++					





Transforming Technology into Art

A visual treat that pleases your eyes and captivates your senses








Smooth Wave grille, Reduced Fan Noise



Decorative Metal Plaque




Geometric Design with Smooth Edges



Environmental-friendly Recyclable Plastics



Detachable Modular Grilles



Invisible Base Brackets

IF Award-Winning, Minimalist & Futuristic Aesthetics

The state-of-the-art design of Hi-Therma II Series conveys our pursuit for sustainability, futurism, and minimalism. It adopts a streamlined geometric design with smooth edges treated with high-quality craftsmanship. The modular grilles is made of environmental-friendly recyclable plastics, with the specially-designed decorative metal plaque on the right side. Whether in residential or commercial spaces, it can seamlessly integrate into the environment.






R290 Eco-Friendly Refrigerant

R290, also known as propane, is an eco-friendly refrigerant that marks a significant step forward for sustainable HVAC solutions. Unlike traditional refrigerants such as R-22 or R-410A which contain ozone-depleting substances or have high global warming potential, R290 offers a much greener alternative with nearly zero (only 0.02) carbon emmissions that contributes to mitigating climate change.

- Zero Ozone Depletion Potential (ODP=0)
- Less charge amount under the same capacity
- ◆ Lower Global Warming Potential (GWP=3)
- Higher Energy Efficiency



Triple Refrigerant Safety Protection

While R290 is classified as a mildly flammable refrigerant, strict safety protection measures are conducted to ensure your peace of mind. The electrical box is fully sealed, and all internal components comply with A3 explosion-proof standard, preventing any electrical ignition in case of refrigerant leaks. Besides, the Water-Refrigerant Separator prevents the refrigerant from entering the living space, further enhancing safety.





Hi-Therma II Reimagine your solution

High SCOP Performance

Boasting a High SCOP Performance of 5.0+, this remarkable rating ensures maximum heating performance while significantly reducing your energy consumption and carbon footprint.




A+++ Energy Efficiency

Hi-Therma II offers the best efficient solution for home heating and hot water supply. It has the top class A+++ energy classification at 35°C and up to A+++ at 55°C, which saves on your energy bills and reduces impact on the environment.




Maxmize Energy Utilization with PV Interlocked

Maximize your energy efficiency with photovoltaic (PV) storage interlocked, ensuring that renewable energy is utilized to its fullest potential, and leading to significant cost savings and environmental benefits.



4 Energy Utilization Scenarios (Optional):




17 – - 18



Consistent Warmth Guaranteed

Our cutting-edge system guarantees stable operation even when the outdoor temperature is as low as -25° C, and 100% heating capacity is guaranteed at -7° C, effortlessly meeting the heating demand in extreme cold areas. With the ability to produce up to 75° C outlet water even at -10° C, you can enjoy health and warmth with effectice sterilization.



Wide Operation Range

Experience ultimate heating and cooling performance in every season, with outdoor ambient temperature range for heating operation from -25° C to 35° C, for domestic hot water from -25° C to 46° C, and for cooling from 5° C to 48° C.




Whisper-quiet Operation

Hi-Therma II Series can work in a low-noise operation mode for optimal user comfort, with max.8 dB(A) can be reduced. Under the night shift mode, the operation period can be set according to individual needs, further lowering the sound pressure level to an ultra-quiet 36dB(A). All these modes can be adjusted with a simple touch on the controller.



Bottom Anti-frosting Design


The specially designed anti-freezing section at the bottom of the heat exchanger prevents frost accumulation, and the bottom plate is equipped with electric heating to prevent ice blockage, maintaining seamless functionality of the unit throughout the year.



21 – – 22


Two Separate Temp. Cycles

Two temperature zones through the separate heating cycles is possible with the mixing valve kit, enabling different water temperatures for underfloor heating and the radiator, providing customized comfort tailored to each area of your home.




Radiator

Floor Heating



8 Rooms Independent Temp. Control


The temperature of up to 8 rooms can be independently controlled through installing temperature sensors or room thermostats in the rooms, satisfying the diverse needs of users.



Note: In one Hi-Therma system, up to 2 room thermostats and max. 6 wall mounted temp. sensors can be connected.


Interlock with 3rd Party Heat Source

Hi-Therma II Series can interlock with the 3rd party heat source, like the solar thermal or the boiler which can work as an auxiliary heat source. Thanks to the interlock design, both the user experience and energy efficiency can be optimized.




Swimming Pool Heating Available







25



27 – – 28

Hi-Therma II Reimagine your solution

Smart Control by App

Whether you're at home or away, Hi-Cube keeps you connected, allowing you to manage and adjust settings effortlessly at anytime and anywhere, ensuring optimal performance and energy efficiency.

- on/off
- •14 languages available

- Multiple scenes setting (timer/holiday mode)
- Temp. setting of rooms, domestic hot water and water cycles Energy management display (daily/weekly/monthly/yearly)



Voice Assistant

When at home, you can wake up Hi-Therma II without having to walk over to it. Enjoy voice-controlled convenience to manage your home with compatibility for Alexa and Google Assistant.

Besides, it can also be compatible with the Connectlife home appliance integration control, where your fridge, washing machine, air conditioner, and more Hisense home appliances can be managed together in the same app.






^{*}Note: ConnectLife is under development and will be available in Q4-2025

Error Reminder

For any issues with Hi-Therma II, you can easily report them for repair with just one tap through the Hi-Mit, enjoying quick responses and professional services.

Our technicians can remotely assist in troubleshooting, reducing your waiting times.



Energy Consumption Visualization

With advanced energy management features, Hi-Therma II enables you to check daily, weekly, and monthly electricity data, and set energy-saving modes accordingly, providing a more economical, efficient, and comfortable home.



USB Plug-and-Play Configuration

One-click Configuration Import: Just plug in the power bank and the unit powers up. With one click, you can import the configuration file, enabling the unit to be quickly activated.

One-click Configuration Export: Copy it to another machine of the same type for direct use, ensuring high operational reliability



* * OTA Remote Upgrade


OTA remote or USB on-site upgrades for both indoor and outdoor units, keeping the system always cutting-edge and future-proof.



^{**}Coming Soon

Data Storage for Worry-free Subsidies

The USB feature can also log and upload the unit's real-time operation data every hour for a period of 10years, which can be used to apply for energy efficiency subsidies from Germany's Federal Office for Economic Affairs and Export Control(BAFA).



31 – 32



Easy Transportation with Compact Body

With only 840mm in height and min.114kg in weight, the Hi-Therma II Series allows for effortless transportation in both small vans and large trucks, making it easy to handle and install.





Easy Installation with Base Brackets

With three independent base brackets, the unit can be easily installed horizontally in different ground conditions without removing the grille.



Detachable Modular Grilles

Previously, it was necessary to dismantle the entire grille when carrying out maintenance, which was time-consuming and troublesome. Now, the modular design allows service providers to remove only the section that needs repair. It not only improves the efficiency and convenience but also reduces the risk of accidental maloperations.




Convenient Curcuit Commissioning

There is no need for refrigerant operation on site, and the installation of the waterway can be completed by only one person, saving valuable time and labor costs while ensuring each component is thoroughly inspected for optimal system reliability.




Integrated Waterway Components

Hi-Therma II series featuring all-in-one design allows easy installation without additional refrigerant piping work and refrigerant charge. Only the connection of water pipes is required on site, which greatly simplifies the on-site installation work.



Wiring Box Connection

The wiring box and the outdoor unit can be connected with just one cable, minimizing wall penetration and shortening total wiring length. It greatly reduces labor and time costs, making it more cost-effective and time-saving than ever before.





Hi-Therma II Reimagine your solution









Specification


	Outd	oor Unit Mode	•		AHZ-050HCPB1A	AHZ-080HCPB1A	AHZ-100HCPB1A	
Power Sup					1N, 220-240V, 50Hz			
	OAT (DB/WB)	IWT / OWT	-	-		Parameters		
			Capacity	kW	5.00	8.00	10.00	
		30 / 35 °C	COP	-	5.20	5.10	4.80	
	7 / 6 °C		Capacity	kW	5.00	8.00	10.00	
ominal Heating Operation*1		47 / 55 °C	COP	-	3.15	3.20	3.10	
offilial Heating Operation*1			Capacity	kW	5.00	8.00	10.00	
		30 / 35 °C	COP	-	3.00	3.00	2.80	
	-7 / -8 °C		Capacity	kW	5.00	7.00	8.00	
		47 / 55 °C	COP	-	2.20	2.15	2.15	
			Capacity	kW	5.50	8.00	9.00	
		12 / 7 °C	EER	_	3.30	3.30	3.30	
ominal Cooling Operation*1	35 / °C		Capacity	kW	5.50	8.00	10.00	
		23 / 18 °C	EER	-	5.20	5.00	4.70	
		SCOP	ELI.	_	5.08	5.05	5.00	
	Water Outlet		ating Efficiency (ηs)	%	200	199	197	
	35°C	Energy Ratir		-	A+++	A+++	A+++	
easonal Performance*2		SCOP	.8	_	3.81	3.93	3.81	
	Water Outlet		ating Efficiency (ηs)	%	149	154	149	
	55°C	Energy Ratir		-	A++	A+++	A++	
	Normal Mode		ig	dB(A)	42	42	43	
ound Pressure*3	Low Noise Mode		dB(A)	38	38	39		
Julia i ressure-s	Night shift Mo			dB(A)	36	36	37	
ound Power	Normal Mode			dB(A)	53	53	54	
Julia i owei	Condenser Fa			GD(A)	1	1	1	
an Air Flow R				m3/h	2870	3780	3780	
uter Dimensions	Height×Width×Depth			mm	2010	845×1376×426	3700	
acking Dimensions	Height×Width			mm		1025×1500×570		
et Weight	Ticigitt* Widti	глосрии		kg	114	122	122	
ross Weight				kg	137	145	145	
1033 Weight			Type	-	137		140	
	Compressor	Compressor Quantity		_		Rotary 1		
			Type	_		1 PAG VG60		
efrigerant System	Refrigeration	Oil	Charge	L	0.6	0.83	0.83	
			Type	-	U.b	0.83 R290	0.83	
	Refrigeration	Charge	Before Shipment	kg	0.90	0.98	0.98	
		Outdoor am	bient temperature	°C (DB)	0.90	-25~35	0.98	
	Heating		temperature	°C		20~75		
			bient temperature	°C (DB)		5~48		
peration Range	Cooling		temperature	°C		5~22		
			bient temperature	°C (DB)		-25~46		
	DHW	Tank water t		°C		-25~46 30~75		
ater Flow Rate	IWT: 30 °C / 0			m3/h	0.86	1.38	1.72	
ater Flow Nate	Type	JVV1. 33 CA	1.5 C	1110/11	0.80		1.72	
	Max. Lift Pres	curo		m		Inverter 9		
C Water pump				m3/h		4.5		
	Max. Water Flow Rate Max. Power Input			W		4.5 95		
		iput		- VV				
alve	Safety Valve					Yes (3 bar)		
	Shut-off Valve			in.		1", DN25		
	Connection ty					Screwed connection		
later Installation	Shutdown valves			mm (in.)		G1"(male)-G1"(female)		
	Inlet pipe diar			mm (in.)		G1"(female)		
	Outlet pipe diameter			mm (in.)		G1"(female)		

Dimensions

Unit: mm







39 -- 40

^{*1:} Heating/Cooling nominal performances at full load conditions according to EN 14511. heating performance are integrated (included defrost cycles).

*2: According to EN14825. Climate Zone AVERAGE. Energy efficiency scale from A +++ to D.

*3: The sound power level is measured according to EN12102 under EN14825 (part load) conditions. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be taken into consideration at the scene. OAT: Outdoor ambient temperature; IWT: Inlet water temperature; OWT: Outlet water temperature





Specification

	Outd	oor Unit Mode	e		AHW-050HCPB1	AHW-080HCPB1	AHW-100HCPE	
Power Supply			1N, 220-240V, 50Hz					
	OAT (DB/WB)	IWT / OWT	-	-		Parameters		
		30 / 35 °C	Capacity	kW	5.00	8.00	10.00	
	7 / 6 °C	30 / 33 -C	COP	-	5.20	5.10	4.80	
	770-0	47 / 55 °C	Capacity	kW	5.00	8.00	10.00	
ominal Heating Operation*1		41733 0	COP	-	3.15	3.20	3.10	
J 1		30 / 35 °C	Capacity	kW	5.00	8.00	10.00	
	-7 / -8 °C	30 / 33 C	COP	-	3.00	3.00	2.80	
	17 0 0	47 / 55 °C	Capacity	kW	5.00	7.00	8.00	
		41733 C	COP	-	2.20	2.15	2.15	
		12 / 7 °C	Capacity	kW	5.50	8.00	9.00	
ominal Cooling Operation*1	35 / °C	12/10	EER	-	3.30	3.15	3.10	
offilial Cooling Operation*1	337 C	23 / 18 °C	Capacity	kW	5.50	8.00	10.00	
		237 10 C	EER	-	5.20	5.00	4.70	
	Water Outlet	SCOP		-	5.08	5.01	4.89	
	35°C	Seasonal He	ating Efficiency (ηs)	%	200	197	192	
easonal Performance*2	33 0	Energy Ratin	ng	-	A+++	A+++	A+++	
asonari eriormance-2	Water Outlet	SCOP		-	3.75	3.73	3.61	
	55°C	Seasonal He	eating Efficiency (ηs)	%	147	146	142	
	55°C	Energy Ratin	ng	-	A++	A++	A++	
	Normal Mode		dB(A)	42	42	43		
ound Pressure*3	Low Noise Mode			dB(A)	38	40	40	
	Night shift Mode			dB(A)	37	38	38	
ound Power	Normal Mode	9		dB(A)	54	54	55	
an	Condenser Fa	Condenser Fan Quantity			1	1	1	
arı	Air Flow Rate			m3/h	2870	3780	3780	
Outer Dimensions	Height×Width	h×Depth		mm		845×1100×426		
acking Dimensions	Height×Width	h×Depth		mm		1135×1235×570		
let Weight				kg	87	95	95	
iross Weight				kg	111	119	119	
			Туре		Rotary	Rotary	Rotary	
	Compressor		Quantity		1	1	1	
ofricarent Custom	Defriesvation	0:1	Туре		PAG VG60	PAG VG60	PAG VG60	
efrigerant System	Refrigeration	OII	Charge	L	0.6	0.83	0.83	
	Refrigeration	Chargo	Туре		R290	R290	R290	
	Reingeration	Charge	Before Shipment	kg	0.90	0.98	0.98	
linimum piping length				m	4	4	4	
	Lloating	Outdoor an	bient temperature	°C (DB)	-25~35	-25~35	-25~35	
	Heating	Outlet wate	r temperature	°C	20~75	20~75	20~75	
	Cooling	Outdoor an	Outdoor ambient temperature		5~48	5~48	5~48	
peration Range	(ooling		r temperature	°C	5~22	5~22	5~22	
			bient temperature	°C (DB)	-25~46	-25~46	-25~46	
			temperature	°C	30~75	30~75	30~75	
ater Flow Rate	IWT: 30 °C / 0	OWT: 35 °C Δ	T: 5 °C	m3/h	0.86	1.38	1.72	
	Connection ty	/pe		-		Screwed connection		
/ater Installation	Shut-off valve			mm (in.)		G 1" (female) - G 1" (female)		
vater mstallation	Inlet pipe diar	Inlet pipe diameter				G 1" (female)		
	Outlet pipe di	iameter		mm (in.)		G 1" (female)		

	Indoor Unit Mode		AHM-100HCWBAA
Power Supply			1N, 220-240V, 50Hz
Outer Dimensions (with connections)	Height×Width×Depth	mm	890×520×320
Packing Dimensions	Height×Width×Depth	mm	419×1160×650
Net Weight		kg	40
Gross Weight		kg	46
	Туре	-	Inverter
DC Water pump	Max. Lift Pressure		9
DC Water pump	Max. Water Flow Rate		4.5
	Max. Power Input	W	95
Valve	Safety Valve		Yes (3 bar)
valve	Shut-off Valve	in.	1", DN25
	Connection type		Screwed connection
	Inlet pipe diameter (from oudoor unit)		G 1" (female)
Piping connection	Outlet pipe diameter (to outdoor unit)		G 1" (female)
	Inlet pipe diameter (from space heating and water heating)		G 1" (female)
	Outlet pipe diameter (to space heating and water heating)		G 1" (female)
Noise level (sound pressure)		dB(A)	30
Noise level (sound power)			44

- *1: Heating/Cooling nominal performances at full load conditions according to EN 14511. heating performance are integrated (included defrost cycles).


 *2: According to EN14825. Climate Zone AVERAGE. Energy efficiency scale from A +++ to D.


 *3: The sound power level is measured according to EN12102 under EN14825 (part load) conditions. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be taken into consideration at the scene.


 OAT: Outdoor ambient temperature; IWT: Inlet water temperature; OWT: Outlet water temperature


Dimensions


Unit: mm











41 -- 42





Specification

	Outd	oor Unit Mod	е		AHW-050HCPB1	AHW-080HCPB1	AHW-100HCPB	
Power Su	oply					1N, 220-240V, 50Hz		
	OAT (DB/WB)	IWT / OWT	-	-		Parameters		
		30 / 35 °C	Capacity	kW	5.00	8.00	10.00	
	7 / 6 °C	30 / 35 -C	COP	-	5.20	5.10	4.80	
	/ / 6 °C	47 / 55 °C	Capacity	kW	5.00	8.00	10.00	
Nominal Heating Operation*1		47 7 55 - C	COP	-	3.15	3.20	3.10	
3 1		30 / 35 °C	Capacity	kW	5.00	8.00	10.00	
	-7 / -8 °C	30 / 33 -C	COP	-	3.00	3.00	2.80	
	-17-0 C	47 / 55 °C	Capacity	kW	5.00	7.00	8.00	
		41733 0	COP	-	2.20	2.15	2.15	
		12 / 7 °C	Capacity	kW	5.50	8.00	9.00	
Nominal Cooling Operation*1	35 / °C	12/10	EER	-	3.30	3.15	3.10	
Norminal Cooling Operation*1	337 0	23 / 18 °C	Capacity	kW	5.50	8.00	10.00	
		23/10-0	EER	-	5.20	5.00	4.70	
	Water Outlet	SCOP		-	5.08	5.01	4.89	
	35°C	Seasonal He	eating Efficiency (ηs)	%	200	197	192	
Seasonal Performance*2	33-0	Energy Ratio	ng	-	A+++	A+++	A+++	
neasonal Ferrormance-2	Water Outlet	SCOP		-	3.75	3.73	3.61	
	55°C	Seasonal He	eating Efficiency (ηs)	%	147	146	142	
	33°C	Energy Ratio	ng	-	A++	A++	A++	
	Normal Mode		dB(A)	42	42	43		
Sound Pressure*3	Low Noise Mode			dB(A)	38	40	40	
	Night shift Mode			dB(A)	37	38	38	
Sound Power	Normal Mode			dB(A)	54	54	55	
-an	Condenser Fan Quantity				1	1	1	
-an	Air Flow Rate	te		m3/h	2870	3780	3780	
Outer Dimensions	Height×Width	n×Depth		mm		845×1100×426		
Packing Dimensions	Height×Width	n×Depth		mm		1135×1235×570		
Net Weight				kg	87	95	95	
Gross Weight				kg	111	119	119	
	Compressor		Туре		Rotary	Rotary	Rotary	
	Compressor		Quantity		1	1	1	
Refrigerant System	Refrigeration	Oil	Туре		PAG VG60	PAG VG60	PAG VG60	
remgerant system	Reiligeration	OII	Charge	L	0.6	0.83	0.83	
	Refrigeration	Chargo	Туре		R290	R290	R290	
	Kelligeration	Charge	Before Shipment	kg	0.90	0.98	0.98	
Minimum piping length				m	4	4	4	
	Heating	Outdoor an	bient temperature	°C (DB)	-25~35	-25~35	-25~35	
	rieauitg	Outlet wate	r temperature	°C	20~75	20~75	20~75	
	Cooling	Outdoor an	bient temperature	°C (DB)	5~48	5~48	5~48	
Operation Range	(ooling		r temperature	°C	5~22	5~22	5~22	
	Outdoor an		bient temperature	°C (DB)	-25~46	-25~46	-25~46	
	DHW	Tank water	temperature	°C	30~75	30~75	30~75	
Vater Flow Rate	IWT: 30 °C / C	DWT: 35 °C Δ	T: 5 °C	m3/h	0.86	1.38	1.72	
	Connection ty	/pe		-		Screwed connection		
Water Installation	Shut-off valve	es		mm (in.)		G 1" (female) - G 1" (female)		
rvator mistaliation	Inlet pipe diameter			mm (in.)		G 1" (female)		
	Outlet pipe di	iameter		mm (in.)		G 1" (female)		

	Indoor Unit Mode		AHS-100HCWBAA-23
Power Supply			1N, 220-240V, 50Hz
Outer Dimensions (with connections)	Height×Width×Depth	mm	1885×590×625
Packing Dimensions	Height×Width×Depth	mm	2070×700×710
Net Weight		kg	121
Gross Weight		kg	141
	Туре	-	Inverter
DC Water pump	Max. Lift Pressure	m	9
DC Water pump	Max. Water Flow Rate	m3/h	4.5
	Max. Power Input		95
Valve	Safety Valve	-	Yes (3 bar)
valve	Shut-off Valve	in.	1", DN25
	Connection type		Screwed connection
	Inlet pipe diameter (from oudoor unit)		G 1" (female)
Piping connection	Outlet pipe diameter (to outdoor unit)	in.	G 1" (female)
	Inlet pipe diameter (from space heating and water heating)	in.	G 1" (female)
	Outlet pipe diameter (to space heating and water heating)	in.	G 1" (female)
	Connection type	-	Screwed connection
DHW pipes connection	Inlet pipe diameter		G 3/4" (female)
	Outlet pipe diameter	in.	G 3/4" (female)
DHW tank rated volume		L	230
Noise level (sound pressure)		dB(A)	28
Noise level (sound power)		dB(A)	44

- *1: Heating/Cooling nominal performances at full load conditions according to EN 14511. heating performance are integrated (included defrost cycles).


 *2: According to EN14825. Climate Zone AVERAGE. Energy efficiency scale from A +++ to D.


 *3: The sound power level is measured according to EN12102 under EN14825 (part load) conditions. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be taken into consideration at the scene.


OAT: Outdoor ambient temperature; IWT: Inlet water temperature; OWT: Outlet water temperature

Dimensions

Unit: mm







Thermal tank

Hot water heating installation options

Why Hot Water Tank is an optimal solution for domestic use?

Whether your requirement is only hot water or integrate it with solar systems, we provide you with unparalleled solutions that prioritize most convenience, energy effectiveness, and reliability.

Convenience

Options are available in stainless steel with capacities of 200 and 300 liters HDHWT-200/300L30HE.

Effectiveness

Top-notch insulation ensures minimal heat loss. It can be used as a single unit or as part of an integrated system.

Reliability

To prevent the growth of bacteria, the unit can heat water up to $75\,^{\circ}$ C at regular intervals.

Hisense

Specification


	Model		HDHWT-200L30HE	HDHWT-300L30HE		
Casing	Colour		Neutral white			
Casing	Material		Epoxy coated steel / Epoxy-coated mild steel			
	Empty weight	kg	49	60		
	Net water volume	L	185	260		
	Material	_	DUPLE	EX 2205		
Tank	Maximum water temperature	°C	7	75		
	Energy efficiency class		В			
	Operating pressure	bar	6			
	max pressure	bar	10			
	Tube material		Stainless steel (SUS316L)			
	Face area	m ²	1.8	2.07		
Heat exchanger	Internal coil volume	L	9.9	11.4		
	Operating pressure	bar	3			
Booster heater	Capacity kW		3			
Power supply	Phase/Frequency/Voltage	V/Hz	1N, 220~240V, 50Hz			
Protection method			Temperature and pressure relief valve (95℃/0.6Mpa)			
Safety Thermostat	Automatic Reset	°C	75			
	Manual Reset	°C	87			

Dimensions

Unit: mm

Reimagine your solution

200L



.....

Engineering Tools

Hi-Therma Designer

Hi-Therma Designer is a specialized program for choosing Hisense ATW heat pump products, enabling an accurate and quick model selection for projects. It's an online tool for quick and easy access, and fully compatible with computer, tablet and smartphone. The user could open and edit the project at any time and anywhere.

User-friendly operation

This program provides a lot of pictures, schemas and explanations. With less input and choice, the user can get the proper selection quickly and easily.

CO₂ emission calculation

The user can calculate the CO₂ emission that can be reduced from conventional heating systems with other energy.

Selection comparison

Through this function, users can compare two different selections for one project, so as to get the best solution.

Energy consumption calculation

The software includes the build-in climate history data for hundreds of cities, which enabling easy load calculation. Furthermore, the user can calculate the annual energy consumption and efficiency.

Noise level assessment

The noise level to the closed house, such as neighbor's house, could be assessed with a simulation according to the outdoor unit installation.

Customization of accessories

The installer can input and customize the accessories which is used to buy locally.

Report

A professional report with full information and quotation can be output to submit to clients. The user can select the part of full size report to make a short report.

https://:www.hitherma-designer.com



Features Overview

Environment Friendly











Energy Saving





ECO Comfort















Easy Use

















Easy Installation

















47 -- 48

NOTE	NOTE

NOTE		

